



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/519,319

01/18/2005

Weishi Li

20296-003US1

9115

26211 7590 01/07/2009
FISH & RICHARDSON P.C.
P.O. BOX 1022
MINNEAPOLIS, MN 55440-1022

EXAMINER

TRAN, DZUNG D

ART UNIT

PAPER NUMBER

2613

NOTIFICATION DATE

DELIVERY MODE

01/07/2009

ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

PATDOCTC@fr.com

Office Action Summary	Application No.	Applicant(s)	
	10/519,319	LI ET AL.	
	Examiner	Art Unit	
	Dzung D. Tran	2613	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 25 August 2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-18 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-18 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1-3, 5-8, 10-12, and 14-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kubo et al. (EP 1054524) in view of Oberg et al. US 6,915,075.

Regarding to claims 1, 6, 10 and 15, Kubo et al. disclose a method/apparatus of a WDM layer-based OchP (Optical Channel Protection) device capable of signal transmission on working channels and routing selection for protection channels between the transferred traffic and the WDM system (see FIG.4) comprising:

a transmitting module (transmitting module having operating channels 1a-4a, switching unit 28a, operating optical terminal unit 21a-24a and standby optical terminal unit 25a and 46a-see FIG.4) and

a receiving module (receiving module having operating optical terminal unit 21b-24b, standby optical terminal unit 25b and 46b, switching unit 28b and operating channels 1b-4b-see FIG.4);

the transmitting module and the receiving module each comprising

N working channels (operating optical terminal 21a-24a of transmitting module and optical terminal unit 21b-24b of receiving module) connected to receiving ends and

Art Unit: 2613

to transmitting ends of N working channels of the WDM system respectively (see FIG.4 where in operating optical terminal 21a-24a of transmitting module and optical terminal unit 21 b-24b of receiving module are connected to transmitting end and receiving end of Mux/Demux 26a and 26b);

M protection channels (standby optical terminal unit 25a and 46a of transmitting module and standby optical terminal unit 25b and 46b of receiving module) connected to receiving ends and to transmitting ends of M protection channels of the WDM system respectively (see FIG.4 where in standby optical terminal unit 25a and 46a of transmitting module and standby optical terminal unit 25b and 46b of receiving module are connected to transmitting end and receiving end of Mux/Demux 26a and 26b);

a switching device (switching unit 28a of transmitting part and switching unit 28b of receiving part) designed to switch signals in the working channels to the protection channels and to switch signals in the protection channels to the working channels; wherein M and N are natural numbers and M in switching unit 28a of transmitting part designed to switch signals in the working channels (operating channel 1a through 4a) to the protection channels when fault occurs on working channels and switching unit 28b of receiving part designed to switch signals in the protection channels to the working channels at the receiving end part and N operating system has $N=4$ which is greater channels assigned than M standby system has $M=2$).

Kubo does not specifically disclose that the switching device designed to switch signals according to switching requests from the WDM system. Oberg, from the same

Art Unit: 2613

field of endeavor, discloses in Figure 2, a switch 23 that selectively switch signals in the working channels to the protection channels and to switch signals in the protection channels to the working channels in according to switching requests from the WDM system (i.e., by a controller that connected to switch 23, 25). Since, it is well known in the art that a controller is needed for a switch to perform the switching function.

It would have been obvious to a person of ordinary skill in the art at the time invention was made to include the teaching of Oberg in the system of Kubo et al.. One of ordinary skill in the art would have been motivated to do that in order to switch a specific working channel to a specific protection channel.

Regarding to claims 2, 7, 11 and 16, Kubo et al. disclose everything claimed as applied above (see claims 1 and 10). In addition, Kubo et al. disclose the WDM layer-based OChP device further includes: wherein M is greater than 1 (see paragraph [0045] and FIG.4 where in standby channel is assigned by M=2).

Regarding to claims 3, 8, 12 and 17, Kubo et al. disclose everything claimed as applied above (see claims 1 and 10). In addition, Kubo et al. disclose the WDM layer-based OChP device further includes: wherein the switching device of the transmitting module comprises N 50:50 couplers (optical Couplers 31a through 34a-see paragraph [0040]; FIG.2 and FIG.4) and an NxM optical switch (combination of optical switches 35a and 36a-see paragraph [0040]; FIG.2 and FIG.4); one of the two output ports of each coupler being connected to a working channel in the WDM system (see paragraph [0040]; FIG.2 and FIG.4 where in one of the two output ports of each optical coupler 31

Art Unit: 2613

being connected to a operating optical signal 41a (operating optical terminal unit 21a) of WDM system), the other of the two output ports being connected to an input port of the NxM optical switch (see paragraph [0040]; FIG.2 and FIG.4 where in other of the two output ports of each optical coupler 31 being connected to an input port of the optical switches 35a and 36a) ; M output ports of the NxM optical switch being connected to the M protection channels of the WDM system respectively (see paragraph [0040]; FIG.2 and FIG.4 where in outputs from optical switches 35a and 36a being connected to the standby optical terminal units 25a and 46a of the WDM system) ; and

wherein the switching device of the receiving module comprises N 50:50 couplers (optical coupler 31a-see paragraph [0040]; FIG.2 and FIG.4) and an MxN optical switch (combination of optical switches 35a and 36a-see paragraph [0040]; FIG.2 and FIG.4), one of the two input ports of each coupler being connected to a working channel in the WDM system (see paragraph [0040]; FIG.2 and FIG.4 where in one of the two output ports of each optical coupler 31 being connected to a operating optical signal 41a (operating optical terminal unit 21b) of WDM system), and the other of the two input ports being connected to an output port of the MxN optical switch (see paragraph [0040]; FIG.2 and FIG.4 where in other of the two output ports of each optical coupler 31 being connected to an output port of the optical switches 35a and 36a) ; M input ports of the MxN optical switch being connected to the M protection channels of the WDM system respectively (see paragraph [0040]; FIG.2 and FIG.4 where in inputs from optical switches 35a and 36a being connected to the standby optical terminal units 25b and 46b of the WDM system).

Art Unit: 2613

Regarding to claims 5 and 14, Kubo et al. disclose everything claimed as applied above (see claim 1 and 10). In addition, Kubo et al. disclose The WDM layer-based OChP further includes: wherein said switching device of said transmitting module comprises an $N \times (N+M)$ optical switch (optical switch 28a), the $N+M$ output ports of the $N \times (N+M)$ optical Switch being connected to the N working channels (operating optical terminal units 21a through 24a) and the M protection channels (standby optical terminal units 25a and 46a) of the WDM system respectively (see FIG.4 where in switching unit 28a has switching function as four operating channels inputs (N) and output four operating optical terminal units and two standby optical terminal units ($N+M$) so that ($N+M$) output ports of the $N \times (N+M)$ optical switches being connected to operating optical terminal units 21a through 24a of the WDM system and standby optical terminal units 25a and 46a of the WDM system respectively); and

wherein the switching device of the receiving module comprises an $(N+M) \times N$ optical switch (optical switch 28b), the $N+M$ input ports of the $(N+M) \times N$ optical switch being connected to the N working channels (operating optical terminal units 21b through 24b) and the M protection channels (standby optical terminal units 25b and 46b) of the WDM system respectively (see FIG.4 where in switching unit 28b has switching function as input four operating optical terminal units and two standby optical terminal units ($N+M$) and outputs four operating channels (N) so that ($N+M$) input ports of the $N \times (N+M)$ optical switches being connected to operating optical terminal units 21b through 24b of the WDM system and standby optical terminal units 25b and 46b of the WDM system respectively).

3. Claims 4, 9, 13 and 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kubo et al. (EP 1054524) in view of Oberg et al. US 6,915,075 and further in view of Frascolla et al. (US Pub Number 2003/0161629).

Regarding to claims 4 and 13, Kubo et al. disclose everything claimed as applied above (see claims 1 and 10). In addition, Kubo et al. disclose the WDM layer- based OChP device further includes: wherein the switching device of the transmitting module comprises N 50:50 couplers (optical couplers, 31a through 34a-see paragraph [0040]; FIG.2 and FIG.4) and an NxM optical switch (combination of optical switches 35a and 36a-see paragraph [0040]; FIG.2 and FIG.4); one of the two output ports of each coupler being connected to a working channel in the WDM system (see paragraph [0040]; FIG.2 and FIG.4 where in one of the two output ports of each optical coupler 31 being connected to a operating optical signal 41a (operating optical terminal unit 21a) of WDM system), the other of the two output ports being connected to an input port of the NxM optical switch (see paragraph [0040]; FIG.2 and FIG.4 where in other of the two output ports of each optical coupler 31 being connected to an input port of the optical switches 35a and 36a) ; M output ports of the NxM optical switch being connected to the M protection channels of the WDM system respectively (see paragraph [0040]; FIG.2 and FIG.4 where in outputs from optical switches 35a and 36a being connected to the standby optical terminal units 25a and 46a of the WDM system) ; and

Art Unit: 2613

wherein the switching device of the receiving module comprises N 50:50 couplers (optical coupler 31a-see paragraph [0040]; FIG.2 and FIG.4) and an MxN optical switch (combination of optical switches 35a and 36a-see paragraph [0040]; FIG.2 and FIG.4), one of the two input ports of each coupler being connected to a working channel in the WDM system (see paragraph [0040]; FIG.2 and FIG.4 where in one of the two output ports of each optical coupler 31 being connected to a operating optical signal 41a (operating optical terminal unit 21b) of WDM system), and the other of the two input ports being connected to an output port of the MxN optical switch (see paragraph [0040]; FIG.2 and FIG.4 where in other of the two output ports of each optical coupler 31 being connected to an output port of the optical switches 35a and 36a) ; M input ports of the MxN optical switch being connected to the M protection channels of the WDM system respectively (see paragraph [0040]; FIG.2 and FIG.4 where in inputs from optical switches 35a and 36a being connected to the standby optical terminal units 25b and 46b of the WDM system).

Even though Kubo et al. disclose N 50:50 coupler couples to NxM optical switch, Kubo et al. fail to specifically disclose N 1x2 switches couples to NxM optical switch. Frascolla et al. disclose the WDM layer-based OChP device further includes: N1x2 optical switches couples to Nx1 optical switch (see FIG.8 where in plurality of 1x2 optical switches).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time invention was made to modify Kubo et al. with the teaching of Frascolla et al. so as to use optical switches 1x2 and increase the protection channels with switching technique

Art Unit: 2613

from working channels to protection channels and vice versa in the WDM transporting system because it would allow the WDM transporting system improving the reliability as the number of protection channels increase and back up for the failure working channels.

Regarding to claims 9 and 18, Frasca et al. and Kubo et al. disclose everything claimed as applied above (see claims 6 and 15). In addition, Kubo et al. disclose routing low-priority traffic via the protection channels when the protection channels do not carry signals (see paragraph [0041] lines 28-29 and FIG.4).

Therefore, it would have been obvious to a person of ordinary skill in the art at the time invention was made to modify Frasca et al. with the teaching of Kubo et al. so as to increase the protection channels with switching technique from working channels to protection channels and vice versa in the WDM transporting system because it would allow the WDM transporting system improving the reliability as the number of protection channels increase and back up for the failure working channels.

Response to Arguments

4. Applicant's arguments with respect to claims 1-18 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

5. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dzung D Tran whose telephone number is (571) 272-3025. The examiner can normally be reached on 9:00 AM - 7:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jason Chan, can be reached on (571) 272-3022. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Dzung Tran

12/25/2008

/Dzung D Tran/

Primary Examiner, Art Unit 2613

Application/Control Number: 10/519,319
Art Unit: 2613

Page 11